

Checkweigher

CSG Series

Yamato

The Yamato CSG and CMG in-motion checkweighers feature tubular stainless steel construction, HACCP compliant design, advanced digital filtering, self diagnostics and an interactive color touch screen. Available options include networking hardware and software, IP 66 seals and bearings, a variety of rejector mechanisms, printers, unified checkweigher/metal detector control, etc. These in-motion checkweighers incorporate 32 bit digital electronics and dedicated strain gauge load cells to provide fast, accurate weight control management.

Options

- Choose between displays that show weight plus accumulated totals, statistical analysis, histogram, averages or limit bars for close monitoring or a large weight only display for distant viewing.
- Splashproof or Washdown - Different models are available to meet your needs.



Reliability you can trust

Features

- Tubular Stainless Steel Construction - HACCP compliant design
- Automatic Tuning - Weighing times, dynamic calibration and digital filter settings are fine tuned and stored for each product and speed by the Auto-tuning function. The display can show each product's weighing wave form.
- Advanced Digital Filtering (ADF) - Our patented ADF technology filters out external vibrations for improved accuracy.
- Product Memory - Up to 99 different product setups and all respective parameters can be stored for instant recall. Product changeover is quick and easy.
- Self Diagnostics - The CSG and CMG will detect a wide range of error conditions, display them upon detection and provide troubleshooting tips for fast resolution.
- Data Management - Comprehensive summaries, x-bar plots, histograms and statistical analysis are all available on the 10.4" interactive color touch screen.
- Cleaning - The conveyors can easily be removed without tools, making cleanup and maintenance quick and easy.
- Several Displays

Specifications

Model	CSG06L	CSG06LW	CSG20L	CSG20LW
Range	6 ~ 600 g	6 ~ 600 g	20 ~ 2000 g	20 ~ 2000 g
Accuracy (best)	+/- 0.2 g	+/- 0.4 g	+/- 0.3 g	+/- 0.5 g
Maximum Speed (packs/min)	330	330	220	220
Increments	0.1 g	0.1 g	0.1 g	0.1 g
Rated Selectivity Range	0 ~ +/- 99.9 g	0 ~ +/- 99.9 g	0 ~ +/- 99.9 g	0 ~ +/- 99.9 g
Product Dimensions (mm)	Length (max)	200	200	300
	Width (max)	160	200	245
	Height (min)	5	5	5
Water Rating		IP 66		IP 66
Power Consumption	300 VA	300 VA	300 VA	300 VA
Power Supply	100, 115, 220, 230, 240 VAC +/- 10%, 50/60 Hz, single phase			
Air Supply	0.5 MPaG (5 kg/cm ² G) 0.1 Nm ³ /min (for rejector)			



GAMMA SCALE™

Weighing Instruments Sales & Service

Tel: (905)455-8333

Fax: (905)455-0658

E-mail: info@gammascale.com

Website: www.gammascale.com

1-888-426-6218 (GAMMA18)

24/7 Service: 416-388-9988